

B1008 MOBILE POS TERMINAL



Specifications

OS	Android 12 OS
Main Chip	Unisoc SC9863 8*1.6G A55 CPU
•	1.6GHz
Frequency RAM	3GB (Optional 4Gb)
	•
ROM	16GB (Optional 64Gb)
LCD Screen	8 inch IPS Display
Display Resolution	800*1280 IPS
Back light Touch Screen	LED
	PCAP, 5 Point
Printer	Paper width:58mm without cutter Max. paper roll diameter:40mm Support Thermal and label printing
SIM	4G:FDD LTE,TD LTE, 3G: WCDMA, 2G: GSM,GPRS
NFC	ISO/IEC 14443 Type A/B,Mifare 1
Voice call	Support
Microphone	Support
Data	Support
SMS & MMS	Support
WIFI Module	2.4Ghz
Bluetooth	4.2
GPS	Support
USB	USB 2.0(OTG)
Speaker	Support
Slot	SIM ×2;Type-C×1
Physical button	Power , Volume +/-, Reset
Battery	Lithium Battery
Battery Capacity	3.8V 6400 (7.4V 3200mAh) Pure Cobalt Lithium, 400Cycle ≥80%, Removable
Temperature	Storage temperature: -10°C-60°C Working Temperature: 0°C-40°C
Power adapter	5V/2A
Optional Features	
Scanner	2D/1D Barcode Scanner with IR Sensor
Fingerprint module	As per requirement
Customer Display	4" LCM Display
Weight	500g (one package box including product is 750g)
,	5. 1 5 · · · · · · · · · · · · · · · · · ·



PoS Tektronics Limited

Rooms 1318-19, 13 / F, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong pcpos@yahoo.com



